

# CREDIT CARD JSscale MANUAL

## PLEASE READ COMPLETE INSTRUCTIONS BEFORE USE

Thank you for purchasing The Jennings Credit Card Scale. With normal care and proper treatment it will provide years of reliable service. Please read all operating instructions carefully. You can contact us at [www.Jscale.com](http://www.Jscale.com)

### KEEP THE FOLLOWING POINTS IN MIND:

- \* If the display becomes locked on Out2 please recalibrate the scale.
- \* Avoid lengthy exposure to extreme heat or cold, your scale works best when operated at normal room temperature. **Always allow the unit to acclimate to a normal room temperature for at least one hour before use.**
- \* Allow sufficient warm up time. Turn the scale On and wait several seconds to give the internal components a chance to stabilize before weighing.
- \* The cleaner the environment the better. Dust, dirt, moisture, vibration, air currents and proximity to other electronic equipment can all cause an adverse effect on the reliability and accuracy of your scale.
- \* Handle with care. Gently apply all items to be weighed onto tray top. Although this scale is designed to be quite durable, try to avoid rough treatment as this may permanently damage the internal sensor and void your warranty.
- \* Avoid shaking, dropping or otherwise shocking the scale. This is a precision instrument and **MUST BE HANDLED WITH EXTREME CARE.**
- \* Only operate the scale on a stable, vibration free surface. **IMPORTANT:** Do not operate near cell phones, radios, computers, or any other electronic device.
- \*\* These electronic scale are precision instruments. Do not operate near an in-use cell phone, cordless phone, radio, computer or other electronic device. These devices emit RF and can cause unstable scale readings. If your scale ever performs poorly, try moving the scale to a different room or location. This is a very precise scale - the display may seem to wander or jump when weighing. This is due to air currents or vibrations. Stable weighing is achieved when the display remains fixed for 3 seconds.

## OPERATION

### Battery Operation:

- 1) Two CR2032 batteries are required.
- 2) To install batteries:
  - a) Release the battery cover by sliding out sideways.
  - b) Place batteries into battery compartment aligned correctly.
  - c) Replace battery cover.

### DO NOT USE EXCESSIVE FORCE & DO NOT PRESS ON THE TRAY!!!

- 3) The scale is now ready for battery operation.

### (Advanced users only) CALIBRATION

**IMPORTANT:** This scale was professionally factory calibrated before shipment and does NOT need to be recalibrated by the end user. However, if you wish to recalibrate your scale we provide these instructions for calibration: Repeat calibration if the scale ever shows Out2. Incorrect calibration can occur if you do not follow the steps exactly. If your scale does not perform accurately, please try replacing your batteries before you calibrate. You will need a 100gram weight to calibrate this scale. *NOTE: if you do not have access to a 100g weight you can purchase one at your local store or in emergency situations you can use 100g of coins or weights (ie 20 US Nickels = 100g) as a 100g weight.*

- 1) Turn the scale OFF and Place the it on a Flat, very stable surface  
**(Be certain the scale is OFF)**
- 2) Press and hold the TARE key for 10 seconds until a random large number appears on the display - then release the key.
- 3) Press & release the TARE key again, the display will show 2Ero and then 100.0
- 4) Gently place a 100 gram weight on the scale and wait 3 seconds.
- 5) Press the TARE key. The display will show CAL and then PASS, calibration is complete. Remove the weight, then Press and hold the key for 5 seconds to turn the scale off.

**NOTE:** if after calibration your scale does not read accurately, this indicates calibration error and the calibration process should be repeated more slowly.

**Please calibrate on a very stable flat surface**

## INACCURACY / ERROR

The primary reasons for inaccuracy or malfunction are low batteries, incorrect calibration, overload or operating on an unstable surface. Please keep this in mind and maintain and operate your scale properly. The scale is a precise instrument and must be handled with the utmost care and caution.

## FEATURE

### \* Power Up Segment Test

When first turning the unit on, all segments of the display will appear as shown below. This display will remain for approximately 2 seconds and then reset to 0.

**1:8:8:8:8**

### \* Overload

When an applied load exceeds the capacity. "EEEE" will appear on the display. Remove the excessive load immediately!

**!Remember: You can permanently damage the scale by overloading it!**

**\* Negative Value**

Any tared value or a value left in memory will be displayed as a negative number once all weight is removed from the unit. Press tare to re-Zero the unit.

**\* Auto off**

An auto shut off feature is provided to conserve battery power. The unit will automatically turn off after approximately 3 minutes of inactivity.

**KEY PAD FUNCTIONS**

**\* MODE**

Unit (mode) selection: Press and hold the left key to change weight unit You can select g (grams), oz (ounces), dwt (pennyweight) or ct (carats).

**\* ON/OFF**

Press this key to turn unit on. Once the unit is on, press and hold the same key for 5 seconds to turn the scale off

**\* Tray Operation:**

The sliding tray of the CCS is designed to protect the scale from accidental overload when it is closed.

Simply slide the cover off of the scale and place it upside-down on the tray. This way you can use it as an expansion tray or to hold loose items. Note, if you wish to re-zero the scale, simply press the TARE key.

To close the cover simply reinstall it, sliding it back into place from back to front.

NOTE: Always close the cover when storing the scale. Please be sure the cover is fully open before operation.

**\* ZERO (TARE)**

After the scale is ON, you can press TARE to reset the scale to zero. This can be used for eliminating from a sample (or a Tray/Container) the weight value of a container weight is permanently removed for the remainder of the procedure. Just turn the scale ON, place the tray or container on weighing platform, and press the TARE key. The scale will show 0.0 (or 0.00) on the display and you can add items to the container/tray.

NOTE: When all weight are removed from the weighing tray, the tared value of a container will be displayed as a negative number. Cycle the power on the scale or press the TARE key to reset the scale to zero.

\*\* These electronic scale are precision instruments. Avoid disturbing environmental conditions such as currents, vibrations, strong electrical and magnetic fields as well as a rapid change of the ambient temperature.

**WARRANTY**

This scale is warranted to the original consumer purchaser from all defects in materials or craftsmanship for **2 years** from the date of purchase. Any defect created by misuse, abuse, overload or physical damage (ie dropping the scale) is not covered. Also any consequential or incidental damage is not covered. Please send your scale via an insured traceable service to be certain it does not get lost in transit. There is a \$10 warranty fee on all returned scales to cover postage and inspection costs.

**We do not accept returns of used scales from our resellers**

You must return all scales directly to our repair center.

**Jennings Warranty Dept  
3402 E Thomas Rd #33  
Phoenix AZ 85018 USA**

Canadian Customers can send their scales to:

**Jennings Canada PO Box 95036 Vancouver BC V6P 6V4**

Please make sure you include your original receipt as proof of purchase.. **NOTE: Because of Enhanced Security measures The scale must be completely clean and devoid of food or lab matter. Unsanitary or unclean scales and scales returned without their original receipt and \$10 fee will be safely destroyed without repair or notification.** We need your receipt to determine the correct start date of your warranty and that you are the original purchaser. Your receipt will be mailed back with your replaced or repaired scale. Please include a note describing the problem with the scale and your return address.